

GF-Slider System


GFM is proud to present the GF-Slider System. It's available in 4 different lengths but the modular design allows you to swap the precision rails, depending on the size required at the time.

The rails are drilled with 3/8" threaded holes spaced 1" apart allowing a range of standard industry accessories to be attached. It mounts on either Euro-adapter or Mitchell as well as having a number of end mounts to choose from.



GF-Slider including:


- 2 precision rails
- 2 end mounts with 360° "tooth system"
- tracking carriage for Mitchell or Bowl mount



AL-2113 100 mm bowl



AL-2114 150 mm bowl




AL-2155 Mitchell Plate




AL-2165 Combi-rig Tube or Double Euro-adapter

The tracking carriage comes with the low height adjuster but additional adjusters are available should the height of the camera mount need to be extended.



AL-2598 Height adjusters



AL-2597 Height adjusters medium



AL-2596 Height adjusters high



AL-2595 Height adjusters extra high

Depending on budget or requirement we offer a choice of mounts to connect the GF-Slider directly on to a Mitchell or Euro-adapter type dolly mount. The Mitchell is available with or without a pan-bearing.



AL-2570 Mitchell mount



AL-2571 Mitchell mount with pan bearing



AL-2571 Mitchell mount female with pan bearing



AL-2580 Euro-adapter mount with pan bearing



Grip Factory Munich GmbH
Fürholzener Straße 1
85386 Eching/Munich
Germany
Tel.: +49 (0)89 / 31 90 12 90
Fax: +49 (0)89 / 31 90 12 99
E-Mail: info@g-f-m.net
Internet: www.g-f-m.net


The side plates combine with the rail mounts to provide, on the one hand, fast horizontal repositioning along the length of the rail and secondly another method to adjust height and therefore clearance of the camera head between the tracking carriage and rail mount.













AL-2586 Side plates for horizontal positioning medium



AL-2587 Side plates for horizontal positioning small

The standard end mount is machined with 360 degree "tooth system" allowing for the connection of various scaffold tube and levelling leg mounts. It's also got a number of 3/8" threaded holes for connecting adapters etc.

As an alternative option we offer the plain end mount for use dolly slider mode. It too has a number of 3/8" threaded holes for connecting adapters etc.



Lighting stand adapter (28mm)



Scaffold tube adapter



Leveling legs with pads



Scaffold tube double mount (adjustable width)



Standard end mount & plain end mount



GF-Combi Rig tube for high and low modes



Horizontal & vertical counterweight rod

