



GF-Track

GF-Track is a dolly and crane track system that perfectly combines the advantages of both aluminium and stainless steel as the working materials.

Standard widths are 62cm (24,5") and 100cm (39").

Standard lengths:

- 90 cm / 3 ft
- 160 cm / 5 ft
- 230 cm / 7,5 ft



Curves are available in 62cm (24,5") width and can be connected to straight track in either a left or right-hand curve.

There are a circle sizes available:

Standard circle:


- Inside diameter 480 cm (16')
- Outside 600 cm (20')

Features:


- Robust design** - a combination of high grade stainless steel tubing mounted on a choice of two hard coated aluminium extrusions
- Stable under heavy loads** - strengthened extrusion and stainless steel tubes result in a strong, stable track
- Foldable or fixed** - straight track is foldable in either direction or can be adjusted to remain fixed.
- Exchangeable end sections** - high grade stainless steel joints, additionally machined for an exact seamless fitting
- High precision** - machine calibrated and ground, stainless steel tubes
- TÜV Certified** - Safety Type Tested

GF-Track	62 cm / 24,5"	100 cm / 39"
90 cm / 3'	8,3 kg / 18,2 lbs	9,9 kg / 21,7 lbs
160 cm / 5'	13,5 kg / 29,7 lbs	15,9 kg / 34,9 lbs
230 cm / 7' 6"	18,9 kg / 41,5 lbs	21,1 kg / 48,6 lbs
Standard curve	18 kg / 39 lbs	

Other lengths and widths upon request



Standard extrusion for dolly track




Strengthened extrusion for crane track



The TÜV SÜD Deutschland have safety type tested and approved the GF-Track according to European guidelines for the scope of application under EC directives. This certification is based on state-of-the-art-technology.



Foldable and lightweight



Precision joints



Dolly stopper



Mounting ramp

GF-Track



Grip Factory Munich GmbH
 Fürholzener Straße 1
 85386 Eching/Munich
 Germany
 Tel.: +49 (0)89 / 31 90 12 90
 Fax: +49 (0)89 / 31 90 12 99
 E-Mail: info@g-f-m.net
 Internet: www.g-f-m.net

Link to website

